

Sigl et al.

S/N: 10/604,252

In the Claims

1 (Currently Amended) An extruded heat sink for use in cooling an electronic component, said heat sink having a body with a flat generally planar surface and two laterally facing exterior surfaces, a plurality of thin fins extending outwardly from said body and being elongated in the direction along said two lateral exterior surfaces, each of said lateral surfaces having elongated ridges formed thereabout extending the full length of said lateral exterior surfaces, the elongated ridges constructed to removably engage a retention means for receiving the heat sink to a frame.

2. (Original) The extruded heat sink of claim 1 wherein said extruded heat sink is aluminum.

3. (Original) The extruded heat sink of claim 1 absent surface machining and absent surface holes therein.

4. (Currently Amended) A heat sink comprising:
a base having a first side and a second side;
a plurality of fins extending from the first side of the base and including a first fin and a last fin; and
a groove formed in the first and the last fin and constructed to engage a retainer therein upon translation of the heat sink relative to the retainer in a direction generally transverse to a length of the groove.

5. (Previously Presented) The heat sink of claim 4 further comprising a second fin extending from the first and the last fins.

6. (Previously Presented) The heat sink of claim 4 wherein the retainer maintains a contact between the second side of the heat sink and a heat generating component.

7. (Previously Presented) The heat sink of claim 4 wherein the groove in the first fin is generally coplanar with the groove formed in the second fin.

BEST AVAILABLE COPY

Sigl et al.

S/N: 10/604,252

8. (Previously Presented) The heat sink of claim 4 where the groove in the first fin and the groove in the second fin are a common distance from the base.

9. (Previously Presented) The heat sink of claim 4 wherein the plurality of fins extend a distance from the base longer than a distance between the first and the last fins.

10. (Previously Presented) The heat sink of claim 4 formed of extruded aluminum.

11. (Previously Presented) The heat sink of claim 4 wherein the plurality of fins are generally perpendicular to the base.

12. (Currently Amended) A heat sink comprising:
a base having a first and a second end;
a pair of external surfaces extending a length above the base having a length and
extending from the first and second ends of the base; and
a plurality of fins extending from the base between the pair of external surfaces;
and extending having a length different than from the length of the external surfaces.

13. (Previously Presented) The heat sink of claim 12 wherein the length of the external surfaces is approximately half the length of the plurality of fins.

14. (Previously Presented) The heat sink of claim 12 further comprising a retainer constructed to engage an end of each of the pair of external surfaces.

15. (Previously Presented) The heat sink of claim 12 wherein the base is constructed to thermally engage an electrical component.

16. (Previously Presented) The heat sink of claim 12 formed of extruded aluminum.

17. (Previously Presented) The heat sink of claim 12 wherein the plurality of fins are generally perpendicular to the base and generally parallel to the external surfaces.

Sigl et al.

S/N: 10/604,252

18. (Previously Presented) The heat sink of claim 12 wherein the external surfaces are generally thicker than the plurality of fins.

19. (Currently Amended) A heat sink assembly comprising:

a heat sink having a base with a pair of generally parallel sides and a first end fin and a second end fin;

a plurality of intermediate fins extending from the base between the first and second end fins ~~generally parallel sides thereof~~; and

a retainer constructed to receive the heat sink therein and removably engage the first and second ends fins of the ~~base~~ heat sink.

20. (Previously Presented) The assembly of claim 19 further comprising a heat generating device in thermal contact with the base.

21. (Previously Presented) The assembly of claim 19 wherein the plurality of fins are generally perpendicular to a section of the base between the pair of generally parallel sides.

22. (Previously Presented) The assembly of claim 19 wherein the heat sink is extruded aluminum.

23. (Currently Amended) The assembly of claim 19 wherein the first end fin and the second end fin ~~pair of generally parallel sides of the base~~ each have a groove formed therein.

24. (Currently Amended) The assembly of claim 19 wherein the plurality of intermediate fins are longer than the first and second end fins ~~pair of generally parallel sides of the base~~.

25. (New) The assembly of claim 19 wherein the retainer is removably engageable to the heat sink by hand and without use of any mounting hardware or tools.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.